



# INTERNATIONAL® 4200

## PRODUCT SPECIFICATIONS

Model Configurations		4200 4x2						Standard	Maximum	
								Front GAW	8,000 lbs	12,000 lbs
								Rear GAW	15,500 lbs	23,000 lbs
								<b>Total GVW</b>	21,500 lbs	35,000 lbs
Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius		
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance	
128	5372	2714	8086	61	100	39	207.0	19ft. 3in.	20ft. 4in.	
140	5439	2698	8137	73	112	39	219.0	20ft. 9in.	21ft. 10in.	
152	5467	2789	8256	85	148	63	255.0	22ft. 3in.	23ft. 4in.	
169	5553	2749	8302	102	165	63	272.0	24ft. 5in.	25ft. 6in.	
175	5583	2735	8318	108	171	63	278.0	25ft. 2in.	26ft. 3in.	
187	5652	2719	8371	120	195	75	302.0	26ft. 8in.	27ft. 9in.	
205	5730	2724	8454	138	213	75	320.0	28ft. 11in.	30ft. 0in.	
217	5755	2809	8564	150	246	96	353.0	29ft. 1in.	30ft. 2in.	
236	5853	2763	8616	169	265	96	372.0	31ft. 4in.	32ft. 6in.	
254	5953	2732	8685	187	283	96	390.0	33ft. 6in.	34ft. 8in.	

		4200 LP 4x2						Standard	Maximum	
								Front GAW	8,000 lbs	8,000 lbs
								Rear GAW	13,660 lbs	19,000 lbs
								<b>Total GVW</b>	19,660 lbs	27,000 lbs
Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius		
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance	
140	5303	2379	7862	73	112	39	219.0	20ft. 10in.	21ft. 11in.	
152	5331	2463	7794	85	148	63	255.0	22ft. 4in.	23ft. 5in.	
169	5416	2422	7838	102	165	63	272.0	24ft. 5in.	25ft. 7in.	
175	5445	2408	7853	108	171	63	278.0	25ft. 2in.	26ft. 4in.	
187	5500	2434	7934	120	195	75	302.0	26ft. 8in.	27ft. 10in.	
205	5596	2391	7981	138	213	75	320.0	29ft. 0in.	30ft. 1in.	
217	5615	2470	8085	150	246	96	353.0	29ft. 2in.	30ft. 3in.	
236	5711	2422	8133	169	265	96	372.0	31ft. 5in.	32ft. 7in.	
254	5810	2390	8200	187	283	96	390.0	33ft. 7in.	34ft. 9in.	

<b>Frame Rails</b>	50,000 PSI 80,000 PSI 120,000 PS	10.125" 9.125" 10.125", 10.250"
<b>Front Axle</b>	International	8,000; 10,000; 11,000; 12,000 lb Capacity
<b>Front Suspension</b>	Parabolic Taper Leaf w/shocks	8,000; 10,000; 11,000; 12,000 lb Capacity
<b>Brakes</b>	Hydraulic Disc, Air	
<b>Steering</b>	Ross, Shepard	
<b>Exhaust System</b>	Frame Mounted Horizontal Muffler Right or Left Side w/ Horizontal or Vertical Tail pipe	
<b>Electrical System</b>	Leece-Neville Delco-Remy America Inc.  International Delphi  Long Life Halogen Headlights	110, 140, 160, 200 Amp Alternators 100, 145 Amp Alternators  1100, 1300, 1950 CCA Battery System 1400, 2100 CCA Battery System
<b>Front End</b>	Tilting Fiberglass Hood With Three Piece Construction Chrome Grille	
<b>Paint</b>	Base Coat / Clear Coat	
<b>Clutch</b>	Eaton Fuller	
<b>Engine &amp; Equipment</b>	International VT365  Air Cleaner	175 HP/460 lb-ft to 230 HP/620 lb-ft  Single/Dual Element w/ optional Integral Snow Valve and In-Cab Control
<b>Transmissions</b>	Fuller Allison	5,6 Speed Manual 2000, 2400 Series Automatic
<b>Rear Axle</b>	International	12,200; 13,500; 15,500; 17,500; 19,000; 21,000; 21,000; 22,000; 23,000 lb Capacity

<b>Single Rear Suspension</b>	International Air Suspension	12,000; 15,500; 18,500 lb Capacity w/5.3" Ride Height
	International Air Suspension	20,000; 21,00 lb Capacity w/9.25" Ride Height
	Spring Suspension	13,500; 15,500; 18,500; 20,000; 23,500; 31,000 lb Capacity Vari-Rate
<b>Fuel Tank</b>	50 – 140 U.S. Gallons Total Capacity	Right or Left, Right and Left Side Under Cab
<b>Cab</b>	Conventional Steel Cab	107.0" BBC
	6-Man Steel Crew Cab	150.9" BBC
	26" Extended	133.0" BBC
	Conventional Steel Cab	
<b>Interior Trim</b>	Deluxe, Premium	
<b>Mirrors</b>	(02) Rectangular w/Breakaway Type Brackets	
<b>Driver Seats</b>	A wide variety of seats including:	<ul style="list-style-type: none"> <li>• Air-Suspension or Non-Suspension, High Back.</li> <li>• Self-Contained w/ Compressor.</li> <li>• Full Width w/ Fixed Mid Back.</li> </ul>
<b>Passenger Seats</b>	A wide variety of seats including:	<ul style="list-style-type: none"> <li>• Two-Man Passenger w/ Storage Compartment</li> <li>• Non-Suspension, High Back</li> <li>• Air-Suspension, High Back</li> </ul>
<b>Front Wheels</b>	Steel, Polished Aluminum	19.5", 22.5"; 8, 10 Stud
<b>Rear Wheels</b>	Steel, Polished Aluminum	19.5", 22.5"; 8, 10 Stud
<b>Tires</b>	Goodyear, Michelin	